CITY OF DOWNEY (PWS 6030012) SOURCE WATER ASSESSMENT FINAL REPORT

November 14, 2000



State of Idaho Department of Environmental Quality

Disclaimer: This publication has been developed as part of an informational service for the source water assessments of public water systems in Idaho and is based on the data available at the time and the professional judgement of the staff. Although reasonable efforts have been made to present accurate information, no guarantees, including expressed or implied warranties of any kind, are made with respect to this publication by the State of Idaho or any of its agencies, employees, or agents, who also assume no legal responsibility for the accuracy of presentations, comments, or other information in this publication. The assessment is subject to modification if new data is produced.

Table of Contents

| 1. Executive Summary | 2 |
|---|----|
| 2. Section 1. Introduction - Basis for Assessment | |
| Level of Accuracy and Purpose of the Assessment | 3 |
| 3. Section 2. Conducting the Assessment | |
| General Description of the Source Water Quality | |
| Defining the Zones of ContributionDelineation | |
| Identifying Potential Sources of Contamination | |
| Contaminant Source Inventory Process | 6 |
| 4. Section 3. Susceptibility Analyses | 8 |
| Hydrologic Sensitivity | |
| Well Construction | |
| Potential Contaminant Source and Land Use | 9 |
| Final Susceptibility Rating | |
| Susceptibility Summary | 9 |
| 5. Section 4. Options for Source Water Protection | 9 |
| 6. Assistance | 11 |
| 7. References Cited | 12 |
| 8. Potential Contaminant Inventory List of Acronyms and Definitions | 13 |
| 9.Attachment A - Susceptibility Worksheet | 14 |
| 10. Figure 1. Geographic Location of the City of Downey | 5 |
| 11. Figure 2. Delineation Map and Potential Contaminant Source Location | 7 |
| 12. Table 1. City of Downey Potential Contaminant Inventory | 6 |
| 13. Table 2. Summary of City of Downey Susceptibility Evaluation | 9 |

Executive Summary

Under the Safe Drinking Water Act Amendments of 1996, all states are required by the U.S. Environmental Protection Agency to assess every source of public drinking water for its relative sensitivity to contaminants regulated by the act. This assessment is based on a land use inventory of the designated assessment area and sensitivity factors associated with the wells and aquifer characteristics.

This report, *Source Water Assessment for the City of Downey* describes the public drinking water system, the boundaries of the zones of water contribution, and the associated potential contaminant sources located within these boundaries. This assessment should be used as a planning tool, taken into account with local knowledge and concerns, to develop and implement appropriate protection measures for this source. The results should <u>not be</u> used as an absolute measure of risk and they should <u>not be</u> used to undermine public confidence in the water system.

The City of Downey water system consists of an unknown number of spring sources and one well source. The spring sources are the City's primary supply of water. The spring sources are located outside the boundary of the Marsh Creek-Lower Portneuf Hydrologic Province and will not be included in this report. However, Idaho Department of Environmental Quality awarded Washington Group International a contract to assess the spring sources. Our office is expecting that information in the Spring of 2002. Once we review the information, a report containing the information will be sent to your water system.

Total coliform bacteria exceeded the Maximum Contaminant Level in the water sampling efforts of September 1996. The inorganic contaminants barium, chromium, fluoride, nitrate, and sodium have been detected in the well water but at levels below the Maximum Contaminant Levels for drinking water. The potential sources of contamination within the delineation capture zones include a sand and gravel mining operation. The final well ranking was moderate for volatile organic contaminants, inorganic contaminants, synthetic organic contaminants, and high for microbial contaminants.

For the City of Downey, source water protection activities should focus on implementation of practices aimed at keeping the distribution system free of microbial contaminants. Disinfection should be considered if microbial problems arise and/or persist. The water system should also be aware of potential risks due to inorganic contaminants (nitrates) and synthetic organic contaminants (herbicides, or pesticides) from agricultural activities in the area of the wellhouse. Land uses within most of the source water assessment area are beyond the control of the City of Downey. Therefore, partnerships with state and local agencies should be established to ensure future land uses are protective of ground water quality. Due to the time involved with the movement of ground water, source water protection activities should be aimed at long-term management strategies even though these strategies may not yield results in the near term. Source water protection activities for agriculture should be coordinated with the Idaho State Department of Agriculture, the Soil Conservation Commission and Portneuf Soil and Water Conservation District, and the Natural Resources Conservation Service.

This assessment should be used as a basis for determining appropriate new protection measures or re-evaluating existing protection efforts. No matter what ranking a source receives, protection is always important. Whether the source is currently located in a "pristine" area or an area with numerous industrial and/or agricultural land uses that require education and surveillance, the way to ensure good water quality in the future is to act now to protect valuable water supply resources.

A community with a fully developed source water protection program will incorporate many strategies. For assistance in developing protection strategies please contact the Pocatello Regional Office of the Idaho Department of Environmental Quality or the Idaho Rural Water Association.

SOURCE WATER ASSESSMENT FOR CITY OF DOWNEY, IDAHO

Section 1. Introduction - Basis for Assessment

The following sections contain information necessary to understand how and why this assessment was conducted. It is important to review this information to understand what the ranking of this source means. A map showing the delineated source water assessment area and the inventory of significant potential sources of contamination identified within that area are contained in this report. The list of significant potential contaminant source categories and their rankings used to develop this assessment is also attached.

Level of Accuracy and Purpose of the Assessment

The Idaho Department of Environmental Quality (DEQ) is required by the U.S. Environmental Protection Agency (EPA) to assess the over 2,900 public drinking water sources in Idaho for their relative susceptibility to contaminants regulated by the Safe Drinking Water Act. This assessment is based on a land use inventory of the delineated assessment area, sensitivity factors associated with the wells, and aquifer characteristics. All assessments must be completed by May of 2003. The resources and time available to accomplish assessments are limited. Therefore, an in-depth, site-specific investigation to identify each significant potential source of contamination for every public water system is not possible. This assessment should be used as a planning tool, taken into account with local knowledge and concerns, to develop and implement appropriate protection measures for this source. The results should not be used as an absolute measure of risk and they should not be used to undermine public confidence in the water system.

The ultimate goal of the assessment is to provide data to local communities to develop a protection strategy for their drinking water supply system. DEQ recognizes that pollution prevention activities generally require less time and money to implement than treatment of a public water supply system once it has been contaminated. DEQ encourages communities to balance resource protection with economic growth and development. The decision as to the amount and types of information necessary to develop a source water protection program should be determined by the local community based on its own needs and limitations. Wellhead or source water protection is one facet of a comprehensive growth plan, and it can complement ongoing local planning efforts.

Section 2. Conducting the Assessment

General Description of the Source Water Quality

The City of Downey is a community public drinking water system serving approximately 625 persons. The water system is located approximately forty miles south of the City of Pocatello in Bannock County (Figure 1). The water system consists of an unknown number of spring sources and one well source. Total coliform bacteria exceeded the Maximum Contaminant Level (MCL) in the water sampling efforts of September 1996. The inorganic contaminants barium, chromium, fluoride, nitrate, and sodium have been detected in the well water but at levels below the MCL for drinking water. Water chemistry tests have not detected volatile organic contaminants (VOCs) or synthetic organic contaminants (SOCs) in the well water. There are no current, long term, recurring water chemistry problems in the drinking water sources. However, there is a possibility of contamination from nearby agricultural activities.

Defining the Zones of Contribution--Delineation

The delineation process establishes the physical area around a well that will become the focal point of the assessment. The process includes mapping the boundaries of the zone of contribution into time of travel zones (zones indicating the number of years necessary for a particle of water to reach a pumping well) for water in the aquifer. Dr. John Welhan of the Idaho Geological Survey used analytical computer models approved by the EPA to determine the 3-year (Zone 1B), 6-year (Zone 2), and 10-year (Zone 3) time of travel zones (TOT) for water associated with the Lower Portneuf River Area.


The computer model used aquifer parameters, such as porosity, and well information, such as well discharge rate and estimates of local hydraulic gradient to calculate the capture zones. The well-specific information was derived from a variety of sources including sanitary surveys, local well logs, and operator records. The actual data used by Dr. Welhan in determining the zones of contribution are available upon request.

In this case where the general source area or ambient direction of ground water flow the well was unknown or could reasonably be assumed to be from two different directions and/or aquifer types, the zones of contribution were calculated for two different cases and both were mapped. The City of Downey well is located in Marsh Valley sedimentary aquifers. The source of recharge for this well may be from tributary valley underflows or from sources upgradient in Marsh Valley.

Identifying Potential Sources of Contamination

A potential source of contamination is defined as any facility or activity that stores, uses, or produces, as a product or by-product, the contaminants regulated under the Safe Drinking Water Act and has a sufficient likelihood of releasing such contaminants at levels that could pose a concern relative to drinking water sources. The goal of the inventory process is to locate and describe those facilities, land uses, and environmental conditions that are potential sources of ground water contamination. The locations of potential sources of contamination within the delineation areas were obtained by field surveys conducted by DEQ and from available databases.

Figure 1 - Geographic Location of the City of Downey



It is important to understand that a release may never occur from a potential source of contamination provided best management practices are used at the facility. Many potential sources of contamination are regulated at the federal level, state level, or both to reduce the risk of release. Therefore, when a business, facility, or property is identified as a potential contaminant source, this should not be interpreted to mean that this business, facility, or property is in violation of any local, state, or federal environmental law or regulation. What it does mean is that the <u>potential</u> for contamination exists due to the nature of the business, industry, or operation. There are a number of methods that water systems can use to work cooperatively with potential sources of contamination, such as educational visits and inspections of stored materials. Many owners of such facilities may not even be aware that they are located near a public water supply well.

Contaminant Source Inventory Process

A two-phased contaminant inventory of the study area was conducted during Fall, 2000. The first phase involved identifying and documenting potential contaminant sources within the City of Downey Source Water Assessment Area through the use of computer databases and Geographic Information System (GIS) maps developed by DEQ. The second or enhanced phase of the contaminant inventory involved contacting the operator to validate the sources identified in phase one and to add any additional potential sources in the areas. This task was undertaken with the assistance of Tony Hancock, City of Downey Maintenance Department.


The City of Downey Source Water Assessment Area has one potential contaminant site within the delineated source water areas. This potential sources of contamination is a sand and gravel mining operation (Table 1). Contaminants of concern are primarily business chemicals such as petroleum products. Table 1 lists the potential contaminants of concern, time of travel zones, and information sources. The well is located approximately 2 miles northeast of the city hall building. The dominant land within the capture zones is agricultural uses.

Table 1. City of Downey Potential Contaminant Inventory

| SITE# | Source Description | TOT Zone (years) | Source of Information | Potential Contaminants |
|-------|----------------------|------------------|-----------------------|---------------------------|
| 1 | Sand and Gravel Mine | 0-3 | Database Inventory | VOC, SOC |

TOT = time of travel (in years) for a potential contaminant to reach the wellhead

VOC = volatile organic chemical, SOC = synthetic organic chemical



Section 3. Susceptibility Analyses

The susceptibility of the well to contamination was ranked as high, moderate, or low risk according to the following considerations: hydrologic characteristics, physical integrity of the well, land use characteristics, and potentially significant contaminant sources. The susceptibility rankings are specific to a particular potential contaminant or category of contaminants. Therefore, a high susceptibility rating relative to one potential contaminant does not mean that the water system is at the same risk for all other potential contaminants. The relative ranking that is derived for the well is a qualitative, screening-level step that, in many cases, uses generalized assumptions and best professional judgement. The following summaries describe the rationale for the susceptibility ranking.

Hydrologic Sensitivity

Hydrologic sensitivity rated moderate for the well source (see Table 2). The soils in the delineation are considered to be in the poor to moderate drainage class. The moderate score reflects the shallow nature of the upper, unconfined ground water system and lack of low permeable units present between the surface and the water producing zone of the aquifer. The well log shows that depth to first ground water is 51 feet.

Well Construction

Well construction directly affects the ability of the well to protect the aquifer from contaminants. System construction scores are reduced when information shows that potential contaminants will have a more difficult time reaching the intake of the well. Lower scores imply a system that can better protect the water. If the casing and annular seal both extend into a low permeability unit then the possibility of cross contamination from other aquifer layers is reduced and the system construction score goes down. If the highest production interval is more than 100 feet below the water table, then the system is considered to have better buffering capacity. When information was adequate, a determination was made as to whether the casing and annular seals extend into low permeability units and whether current public water system (PWS) construction standards are met.

The well system construction rating is low for the well source (Table 2). The low score reflects the casing and annular seal extend into a low permeable unit and the wellhead and surface seal are in compliance with DEQ regulations. The well is housed inside a wellhouse and located outside the 100-year flood plain.

The Well was given an additional point because it does not meet current well construction standards. The Idaho Department of Water Resources (IDWR) *Well Construction Standards Rules (1993)* require all public water systems (PWSs) to follow DEQ standards. IDAPA 58.01.08.550 requires that PWSs follow the *Recommended Standards for Water Works (1997)* during construction. Various aspects of the standards can be assessed from well logs. Table 1 of the *Recommended Standards for Water Works (1997)* states that 22-inch steel casing requires a thickness of 0.500 and 16-inch casing requires a thickness of 0.375. For Well #1, the thickness of the 22-inch and 16-inch steel casings are 0.375. The standards state that screen will be installed and have openings based on sieve analysis of the formation. Standard 3.2.4.1 requires all PWSs to have yield and drawdown tests that last "24 hours or until stabilized drawdown has continued for six hours at 1.5 times the design pumping rate" (Recommended Standards for Water Works, 1997).

Potential Contaminant Source and Land Use

The well rated moderate for inorganic chemicals (IOCs) (i.e. barium, nitrate, chromium, sodium) and low for synthetic organic chemicals (SOCs) (i.e. pesticides), volatile organic chemicals (VOCs) (i.e. petroleum products) and microbial contaminants. Total coliform bacteria exceeded the MCL in the water sampling efforts of September 1996. The dominant land uses within the capture zones is agricultural.

Final Susceptibility Rating

A detection above a drinking water standard Maximum Contaminant Level (MCL), any detection of a VOC or SOC, or a detection of total coliform or fecal coliform will automatically give a high susceptibility rating to the final well ranking despite the land use of the area because a pathway for contamination already exists. In this case, the final well ranking was moderate for VOC, IOC, and SOC contaminants and high for microbial contaminants.

Table 2. Summary of City of Downey Susceptibility Evaluation

| | Susceptibility Scores | | | | | | | | | |
|------|---------------------------|--------------------------|-----|-----|------------------------|------------------------------|-----|-----|-----|------------|
| | Hydrologic Sensitivity | Contaminant Inventory | | | System Construction | Final Susceptibility Ranking | | | | |
| Well | | IOC | VOC | SOC | Microbials | | IOC | VOC | SOC | Microbials |
| 1 | M | M | L | L | L | L | M | M | M | H* |

H = High Susceptibility, M = Moderate Susceptibility, L = Low Susceptibility

IOC = inorganic chemical, VOC = volatile organic chemical, SOC = synthetic organic chemical

 H^* - Indicates source automatically scored as high susceptibility due to presence of microbial contaminant above the maximum contaminant level in the tested drinking water

Susceptibility Summary

DEQ records indicate no detection of a VOC or SOC contaminant in the drinking water. The system has one total coliform bacteria MCL violation since 1996. This total coliform bacteria MCL violation accounts for the high rating in the final susceptibility ranking.

Section 4. Options for Source Water Protection

The susceptibility assessment should be used as a basis for determining appropriate new protection measures or re-evaluating existing protection efforts. No matter what the susceptibility ranking a source receives, protection is always important. Whether the source is currently located in a "pristine" area or an area with numerous industrial and/or agricultural land uses that require education and surveillance, the way to ensure good water quality in the future is to act now to protect valuable water supply resources.

An effective source water protection program is tailored to the particular local source water protection area. A community with a fully developed source water protection program will incorporate many strategies. For the City of Downey, source water protection activities should focus on implementation of practices aimed at keeping the distribution system free of microbial contaminants. Disinfection should be considered if microbial problems arise and/or persist. The water system should also be aware of potential risks due to inorganic contaminants (nitrates, herbicides, or pesticides) from agricultural activities in the area of the wellhouse. Land uses within most of the source water assessment area are beyond the control of the City of Downey. Therefore, partnerships with state and local agencies should be established to ensure future land uses are protective of ground water quality. Due to the time involved with the movement of ground water, wellhead protection activities should be aimed at long-term management strategies even though these strategies may not yield results in the near term. Source water protection activities for agriculture should be coordinated with the Idaho State Department of Agriculture, the Soil Conservation Commission and Portneuf Soil and Water Conservation District, and the Natural Resources Conservation Service.

Assistance

Public water supplies and others may call the following DEQ offices with questions about this assessment and to request assistance with developing and implementing a local protection plan. In addition, draft protection plans may be submitted to the DEQ office for preliminary review and comments.

Pocatello Regional DEQ Office (208) 236-6160

State DEQ Office (208) 373-0502

Website: http://www2.state.id.us/deq

Water suppliers serving fewer than 10,000 persons may contact John Bokor, Idaho Rural Water Association, at 1-800-962-3257 for assistance with wellhead protection strategies.

References Cited

Great Lakes-Upper Mississippi River Board of State and Provincial Public Health and Environment Managers, 1997. "Recommended Standards for Water Works."

Idaho Department of Environmental Quality. 1997. Design Standards for Public Drinking Water Systems. IDAPA 58.01.08.550.01.

Idaho Department of Water Resources, 1993. Administrative Rules of the Idaho Water Resource Board: Well Construction Standards Rules. IDAPA 37.03.09.

Idaho Department of Environmental Quality. 2000. Sanitary Survey Report for City of Downey

Welhan, J. 2000. Idaho Geologic Survey. SWA Capture Zone Delineations, Lower Portneuf and Marsh Valleys

POTENTIAL CONTAMINANT INVENTORY LIST OF ACRONYMS AND DEFINITIONS

<u>AST (Aboveground Storage Tanks)</u> – Sites with aboveground storage tanks.

<u>Business Mailing List</u> – This list contains potential contaminant sites identified through a yellow pages database search of standard industry codes (SIC).

<u>CERCLIS</u> – This includes sites considered for listing under the <u>Comprehensive Environmental Response</u> <u>Compensation and Liability Act (CERCLA)</u>. CERCLA, more commonly known as "Superfund" is designed to clean up hazardous waste sites that are on the national priority list (NPL).

<u>Cyanide Site</u> – DEQ permitted and known historical sites/facilities using cyanide.

<u>Dairy</u> – Sites included in the primary contaminant source inventory represent those facilities regulated by Idaho State Department of Agriculture (ISDA) and may range from a few head to several thousand head of milking cows.

<u>Deep Injection Well</u> – Injection wells regulated under the Idaho Department of Water Resources generally for the disposal of stormwater runoff or agricultural field drainage.

Enhanced Inventory – Enhanced inventory locations are potential contaminant source sites added by the water system. These can include new sites not captured during the primary contaminant inventory, or corrected locations for sites not properly located during the primary contaminant inventory. Enhanced inventory sites can also include miscellaneous sites added by the Idaho Department of Environmental Quality (IDEQ) during the primary contaminant inventory.

Floodplain – This is a coverage of the 100-year floodplains.

<u>Group 1 Sites</u> – These are sites that show elevated levels of contaminants and are not within the priority one areas.

<u>Inorganic Priority Area</u> – Priority one areas where greater than 25% of the wells/springs show constituents higher than primary standards or other health standards.

<u>Landfill</u> – Areas of open and closed municipal and non-municipal landfills.

<u>LUST (Leaking Underground Storage Tank)</u> – Potential contaminant source sites associated with leaking underground storage tanks as regulated under RCRA.

<u>Mines and Quarries</u> – Mines and quarries permitted through the Idaho Department of Lands.)

<u>Nitrate Priority Area</u> – Area where greater than 25% of wells/springs show nitrate values above 5mg/l.

NPDES (National Pollutant Discharge Elimination System) – Sites with NPDES permits. The Clean Water Act requires that any discharge of a pollutant to waters of the United States from a point source must be authorized by an NPDES permit.

<u>Organic Priority Areas</u> – These are any areas where greater than 25 % of wells/springs show levels greater than 1% of the primary standard or other health standards.

<u>Recharge Point</u> – This includes active, proposed, and possible recharge sites on the Snake River Plain.

RICRIS – Site regulated under **Resource Conservation Recovery Act (RCRA)**. RCRA is commonly associated with the cradle to grave management approach for generation, storage, and disposal of hazardous wastes.

SARA Tier II (Superfund Amendments and Reauthorization Act Tier II Facilities) – These sites store certain types and amounts of hazardous materials and must be identified under the Community Right to Know Act.

<u>Toxic Release Inventory (TRI)</u> – The toxic release inventory list was developed as part of the Emergency Planning and Community Right to Know (Community Right to Know) Act passed in 1986. The Community Right to Know Act requires the reporting of any release of a chemical found on the TRI list.

<u>UST</u> (<u>Underground</u> <u>Storage</u> <u>Tank</u>) – Potential contaminant source sites associated with underground storage tanks regulated as regulated under RCRA.

<u>Wastewater Land Applications Sites</u> – These are areas where the land application of municipal or industrial wastewater is permitted by IDEQ.

<u>Wellheads</u> – These are drinking water well locations regulated under the Safe Drinking Water Act. They are not treated as potential contaminant sources.

NOTE: Many of the potential contaminant sources were located using a geocoding program where mailing addresses are used to locate a facility. Field verification of potential contaminant sources is an important element of any enhanced inventory

Attachment A

City of Downey
Susceptibility Analysis
Worksheet

The final scores for the susceptibility analysis were determined using the following formulas:

- 1) VOC/SOC/IOC Final Score = Hydrologic Sensitivity + System Construction + (Potential Contaminant/Land Use x 0.2)
- 2) 2) Microbial Final Score = Hydrologic Sensitivity + System Construction + (Potential Contaminant/Land Use x 0.35)

Final Susceptibility Scoring:

- 0 5 Low Susceptibility
- 6 12 Moderate Susceptibility
- ≥ 13 High Susceptibility

Public Water System Name :

DOWNEY CITY OF

Public Water System Number 6030012

1. System Construction Drill Date Driller Log Available Sanitary Survey (if yes, indicate date of last survey) YES 2000 Well meets IDWR construction standards NO 1 Wellhead and surface seal maintained YES Casing and annular seal extend to low permeability unit YES Ω Highest production 100 feet below static water level Well located outside the 100 year flood plain 2. Hydrologic Sensitivity Soils are poorly to moderately drained YES 0 Vadose zone composed of gravel, fractured rock or unknown NO Ω Depth to first water > 300 feet Aguitard present with > 50 feet cumulative thickness Total Hydrologic Score 3 SOC Microbial TOC VOC Score Score Score 3. Potential Contaminant / Land Use - ZONE 1A Land Use Zone 1A IRRIGATED PASTURE Farm chemical use high NO IOC, VOC, SOC, or Microbial sources in Zone 1A YES Potential Contaminant / Land Use - ZONE 1B Contaminant sources present (Number of Sources) YES 0 1 1 (Score = # Sources X 2) 8 Points Maximum 0 2 2 Ω Sources of Class II or III leacheable contaminants or 1 0 4 Points Maximum Zone 1B contains or intercepts a Group 1 Area 4 Land use Zone 1B Greater Than 50% Irrigated Agricultural Land 8 7 6 4 Total Potential Contaminant Source / Land Use Score - Zone 1B ______ Potential Contaminant / Land Use - ZONE II Contaminant Sources Present II leacheable contaminants or YES 1 0 Land Use Zone II Greater Than 50% Non-Irrigated Agricultural 1 1 Sources of Class II or III leacheable contaminants or Potential Contaminant Source / Land Use Score - Zone II 2 1 1 0 Potential Contaminant / Land Use - ZONE III Contaminant Source Present 0 0 0 Sources of Class II or III leacheable contaminants or Is there irrigated agricultural lands that occupy > 50% of YES 1 1 Total Potential Contaminant Source / Land Use Score - Zone III 2 1 1 0 Cumulative Potential Contaminant / Land Use Score 4. Final Susceptibility Source Score 5. Final Well Ranking Moderate Moderate High

Well# : WELL #1

11/2/00 8:27:29 AM